



Motor Rated Power			16000W	
Inverter Power Supply			400Vdc	
Description	Symbol	Unit		
Duty	-	-	S2-60'	
Nominal Speed	n_n	rpm	3500	
Frequency (N° poles)	$f (2p)$	Hz	233.3 (8)	
Constant Voltage	K_e	Vrms/Krpm	72.0	
Instant Torque	T_i	Nm	122.0	
Instant Current	I_i	Arms	140.0	
Peak Torque S2-5'	T_p	Nm	80.0	
Peak Current S2-5'	I_p	Arms	80.0	
Peak Torque S2-30'	T_p	Nm	59.0	
Peak Current S2-30'	I_p	Arms	56.0	
Rated Torque S2-60'	T_r	Nm	44.0	
Rated Current S2-60'	I_r	Arms	40.0	
Short Circuit Current	I_{sc}	Arms	53.0	
Rotor Inertia	J_r	kg x m ²	0.016	
Ambient Temperature	θ_a	°C	-15 ÷ +40	
Protection Degree	IP		IP 54	up to IP67
Insulation Class	-	-	F	
Thermal protection	-	-	PTY 84-130	Alternative to KTY 84-130

Speed-Torque & Speed Power Motor Curves (*)

SMAC 200-105



Current Map [Arms]



* MTPA – MTPV Field Weakening strategy control & Optimized Advance Angle
(Ref. Simulation temperature 20.0°C)

Simulation Only

Efficiency Map % (*)

