



ELECTRIC POWERTRAIN SOLUTIONS

SMAC SERIE
TECHNICAL DATA SHEET
3-PHASE SYNCHRONOUS MOTOR

Code	51J20021019MT080400		
Rev.	00		
Date	03/03/2021		
Page	1	di	2


Motor Rated Power			20000W	
--------------------------	--	--	---------------	--

Inverter Power Supply			120Vdc	
------------------------------	--	--	---------------	--


Description	Symbol	Unit		
Duty	-	-	S2-60min	
Nominal Speed	n_n	rpm	2000	
Frequency (N° poles)	$f (2p)$	Hz	133.3 (8)	
Costant Voltage	K_e	Vrms/Krpm	28.0	
Costant Torque	K_t	Nm/Arms	0.46	
Instant Torque	T_i	Nm	265.0	
Instant Current	I_i	Arms	730.0	
Peak Torque S2-5min.	T_p	Nm	180.0	
Peak Current S2-5min.	I_p	Arms	420.0	
Rated Torque S2-60min.	T_r	Nm	95.0	
Rated Current S2-60min.	I_r	Arms	210.0	
Rotor Inertia	J_r	kg x m ²	0.036	
Ambient Temperature	θ_a	°C	-15 ÷ +40	
Protection Degree	IP		IP 54	up to IP67
Insulation Class	-	-	F	
Thermal protection	-	-	KTY 84-130	
Cooling system			Air	

Speed-Torque & Speed Power Motor Curves (*)

SMAC 200 210



Efficiency Map % (*)



* MTPA / MTPV Field Weakening strategy control & Optimized Advance Angle